



"Quality Made, Built To Last"

Loading Dock Equipment

***Three Generations Of
Quality Service
Since 1940***



Featured Product:

Guardian 3-in-1 Dor-Seal System

In this catalog:

***Dock Levelers
Truck Restraints
Dock Seals
Dock Shelters
Accessories***



“Quality Made, Built To Last”



Welcome To Chalfant...

At Chalfant we are pleased to bring you a full range of Loading Dock Equipment; Dock Seals, Dock Levelers, Safety Trailer Restraints and associated products. Chalfant has pioneered, developed and provided the industry with quality equipment since 1940. Safe, affordable, reliable dock equipment to meet your specific application needs each and every time.

Improve Employee Safety, Reduce Heating And Cooling Costs, And Protect Products From The Weather

Chalfant door seals, dock shelters and rail shelters are foremost in the industry. They offer unmatched sealing efficiency and durability and are cost effective. Energy savings alone often pay for these products in an amazingly short time.

Guardian 3-in-1 Dor-Seal System

Innovative New Design! Protects Employees And Discourage Pilferage

The Guardian 3-in-1 Dor-Seal System unique triple duty design, keeps conditioned air and packages in and keeps people out. Let your unattended dock be a safe experience against thieves, who can cut through an ordinary foam core of a dock seal. The Guardian 3-1 Dor-Seal System can prevent unauthorized entry and is available with three (3) basic selectable features:

1. Chain-Link Cladding...

Vinyl coated chain-link structure surrounds the foam padding to keep thieves from cutting through the pad to gain access to the trailer and your facility.

2. Unique Mounting Plate...


Heavy-duty wood or optional steel substructure lends stability and rigidity to the dock seal and provides a strong, secure connection to the mounting brackets.

3. Foam Backing...

Soft foam conforms to irregularities of building walls, providing an air and water-tight seal between the dock pad and the building wall.

Quality Construction

Chalfant dock seals are factory assembled and mounted to kiln dried 2" wood and feature "Weatheright Construction" completely encased inside of the pad cover to protection it from abuse and outside elements. Galvanized steel mounting brackets are available in various sizes for different types of building applications and types of pads. All brackets are bolted to the dock door frame. The Dor-Seal pads are positioned in the brackets and attached with lag bolts providing a secure connection to the building and allows quick removal of old units and install of new.



Chalfant Dock Seals

Series 100 Standard

Series 101 & 103 Curtain

Series 200 Adjustable

Series 300 L-Pad



Shown With Wear Pleats
Full Length Guide Stripe



Shown With
Full Length Guide Stripe



Shown With
Full Length Guide Stripe



Shown With
Wear Pleats

Series 100, Standard seals are designed to fit most standard door sizes. Ideal door size 8' x 8' to 9' x 9' with 4" to 6" seal past bumper.

Short Specification

Dock seal Series 100, Standard Model _____, as manufactured by Chalfant Sewing Fabricators, Inc, PH 216-521-7922, to fit door opening _____" wide by _____" high. Base cover fabric to be _____; Contact face fabric (wear face) to be _____; and color of fabric to be _____. Guide stripe shall be 22 oz. vinyl-coated nylon color to be yellow

Series 101 & 103, Curtain seals are designed to fit doors higher than 9 ft. Ideal door size 8' x 9' to 9' x 10' with 4" to 6" seal past bumper.

Short Specification

Dock seal Series 100/103, Curtain Model _____, as manufactured by Chalfant Sewing Fabricators, Inc, PH 216-521-7922, to fit door opening _____" wide by _____" high. Base cover fabric to be _____; Contact face fabric (wear face) to be _____; and color of fabric to be _____. Guide stripe shall be 22 oz. vinyl-coated nylon color to be yellow.

Series 200, Adjustable seals are designed to fit most standard door sizes. Ideal door size 8' x 9' to 9' x 10' with 4" to 6" seal past bumper.

Short Specification

Dock seal Series 200, Adjustable Model _____, as manufactured by Chalfant Sewing Fabricators, Inc, PH 216-521-7922, to fit door opening _____" wide by _____" high. Base cover fabric to be _____; Contact face fabric (wear face) to be _____; and color of fabric to be _____. Guide stripe shall be 22 oz. vinyl-coated nylon color to be yellow

Series 300, L-Pad seals are designed to fit most standard door sizes. Ideal door size 8' x 8' to 10' x 10' with 10" to 12" seal past bumper.

Short Specification

Dock seal Series 300, L-Pad Model _____, as manufactured by Chalfant Sewing Fabricators, Inc, PH 216-521-7922, to fit door opening _____" wide by _____" high. Base cover fabric to be _____; Contact face fabric (wear face) to be _____; and color of fabric to be _____. Guide stripe shall be 22 oz. vinyl-coated nylon color to be yellow.



Select Base Face Fabric And Unit Color:

- | | | | | | | |
|--------------------------------------|--------------------------------------|--|--|---|---|--|
| <input type="checkbox"/> 22 oz Vinyl | <input type="checkbox"/> 40 oz Vinyl | <input type="checkbox"/> 16 oz Hypalon | <input type="checkbox"/> 40 oz Hypalon | <input type="checkbox"/> 16 oz Neoprene | <input type="checkbox"/> 40 oz Neoprene | <input type="checkbox"/> High-Tear Resistant Guardian 60 |
| <input type="checkbox"/> Black | <input type="checkbox"/> Black | <input type="checkbox"/> Black | <input type="checkbox"/> Black | <input type="checkbox"/> Black | <input type="checkbox"/> Black | <input type="checkbox"/> Black |
| <input type="checkbox"/> Blue | <input type="checkbox"/> Blue | <input type="checkbox"/> Blue | <input type="checkbox"/> Tan | | | |
| <input type="checkbox"/> Tan | <input type="checkbox"/> Tan | <input type="checkbox"/> Green | <input type="checkbox"/> Brown | | | |
| <input type="checkbox"/> Green | <input type="checkbox"/> Brown | <input type="checkbox"/> Brown | | | | |
| <input type="checkbox"/> Brown | | | | | | |

Select Contact Face Option:

- Wear Face Guardian Face Guardian Pleat GP4 Guardian Pleat GP8 Guardian Pleat GP16

Note: See Main Catalog For Actual Colors. Samples Of Materials Are Available Upon Request Consult Factory For Other Available Colors.



Select Contact Fabric:

- 22 oz Vinyl 40 oz Vinyl 16 oz Hypalon 40 oz Hypalon 16 oz Neoprene 40 oz Neoprene High-Tear Resistant Guardian 60


Chalfant Rail and Truck Shelters

Series 400 Soft Seal

Series 500 Rail

Series 700 Flex

Series 700 Shelter



Series 400, Soft Seals are designed to fit most standard door sizes. Ideal door size up to 12' x 12' with 4" to 6" seal past bumper.

Short Specification

Dock seal Series 400, Soft Seal Model _____, as manufactured by Chalfant Sewing Fabricators, Inc., 216-521-7922, to fit door opening _____" wide by _____" high. Base cover fabric to be _____. Contact face fabric (wear face) to be _____. Guide stripe shall be 22 oz. vinyl-coated nylon color to be yellow.

Series 500, Rail Shelter are designed to fit most standard door sizes. Ideal door size up to 15' x 15' with 10" to 12", with projection as much as 84".

Short Specification

Dock seal Series 500, Rail Model _____, as manufactured by Chalfant Sewing Fabricators, Inc., PH 216-521-7922 to fit door opening _____" wide by _____" high. Base cover fabric to be _____. Guide stripe shall be 22 oz. vinyl-coated nylon color to be yellow.

Series 700, Flex Shelter are designed to fit most standard door sizes. Ideal door size up to 12' x 12' with minimum to 12", with 12" projection past bumper.

Short Specification

Dock seal Series 700, Flex Model _____, as manufactured by Chalfant Sewing Fabricators, Inc., PH 216-521-7922 to fit door opening _____" wide by _____" high. Base cover fabric to be _____. Guide stripe shall be 22 oz. vinyl-coated nylon color to be yellow.

Series 700, Rigid Shelter are designed to fit most standard door sizes. Ideal door size up to 12' x 12' with minimum to 12", with 12" projection past bumper.

Short Specification

Dock seal Series 700, Flex Model _____, as manufactured by Chalfant Sewing Fabricators, Inc., PH 216-521-7922 to fit door opening _____" wide by _____" high. Base cover fabric to be _____. Guide stripe shall be 22 oz. vinyl-coated nylon color to be yellow.

Fabrics:

Fabric's are available in a wide range of material from vinyl, hypalon, neoprene and "High Tear Resistant Guardian 60", as well as, colors and available weights, as shown below



MATERIAL	TONGUE TEAR STRENGTH	ABRASION RESISTANCE	COLD TEST (-40°F)
22 oz Vinyl	110 lbs x 110 lbs	4,000 Cycles	Pass
40 oz Vinyl	176 lbs x 154 lbs	9,000 Cycles	Pass
16 oz Hypalon	50 lbs x 40 lbs	300 Cycles	Pass
40 oz Hypalon	50 lbs x 50 lbs	1,500 Cycles	Pass
16 oz Neoprene	65 lbs x 55 lbs	1,075 Cycles	Pass
40 oz Neoprene	45 lbs x 38 lbs	300 Cycles	Pass
High Tear G60	176 lbs x 154 lbs	10,000 Cycles	Pass

The information supplied herein is based upon information currently available on the subject. It is offered as a possible helpful guide. Chalfant Sewing Fabricators, inc., makes no guarantee of results and assumes no obligation or liability whatsoever in connection with this information.

Chalfant Dock Levelers & Restraints

Hydraulic Dock Levelers H1 Series, H2 Series



- Simple Push-Button Operation
- Deck & Lip Of 55,000 lbs Minimum Yield
- Continuous Hinge Design With Grease Fittings & Dock Bumpers Standard
- Regenerative Main And Lip Cylinders
- Fall-Safe Prevents Sudden Fall Of Deck
- Hydraulic - 1 HP, 1 GPM Pump/Motor
- Full Range Toe Guards

Mechanical Dock Levelers MPL Series, C Series



- Simple Pull Chain Operation
- Deck & Lip Of 55,000 lbs Minimum Yield
- Continuous Hinge Design With Grease Fittings & Dock Bumpers Standard
- Positive Hold-down Device
- Operating Range +/-12
- Safety Legs Support In Sudden Fall Of Dock
- Maintenance Strut

Edge-Of-Dock Levelers Mechanical, Hydraulic



- Simple Operation
- Continuous Hinge Design With Dock Bumpers Standard
- Mechanical and Hydraulic E.O.D. Levelers raise and extend smoothly onto truck bed
- Both Mechanical and Hydraulic E.O.D. Levelers are easy to recycle with truck in position and automatically return to stored position upon truck departure.

Stronger Steel Means Longer Life

We offer a broad range of affordable, dependable levelers, reliable safety restraints and accessories, quality built and ready to serve your loading dock application. Our high strength steel tread plate, (55,000 lbs. minimum yield) on deck and lip ensures long life stability and durability in all our levelers. Chalfant dock equipment is long lasting, safe, dependable, easy to install, operate, and easy to maintain. Our competitively priced dock equipment will keep your loading dock running safely, smoothly and on schedule every day.

Cost Effective

High Quality Dock Safety

Chalfant offers full range of manual restraints to automatic push-button activated restraints, to protect your loading dock operation with 50,000 lbs. of holding strength for additional safety against unexpected truck departure at the loading dock. All Chalfant Truck Restraints meet 1998 ICC regulations. Both manual and automatic truck restraints provide low-maintenance non-impact design and float effortlessly up and down with truck movement. Constructed of heavy, high strength steel for longer life and protection from accidental damage, periodic lubrication is the only maintenance necessary!

Complete Visual Communication Package



Dependable, Affordable Safety That's Easy To Install.

Bolt-hole pattern design provides optimal holding force. Mounts directly to face of new or existing dock using eight (8) anchor bolts and two (2) ground anchors. Installs in approximately one (1) hour!

Simple Operation



Positive Contact Hook captures and holds all legal ICC Bars.

Chalfant Accessories

Chal-Strip Door Closure PVC Strip Doors



Model	Use	Strip Width	Strip Thickness	% Overlap	Max. Height Ft. interior/exterior	Material	Reinforced	Approvals	Operating Temp. of max/min	
1050	Personnel Door	6 0	0.060	60	4	N/A	Clear PVC	No	FDA	+160/-20
1000	Indoor	8 0	0.080	60	8	N/A	Clear PVC	No	FDA	+1601/-20
1001	Indoor/Outdoor	8 0	0.080	100	8	8	Clear PVC	No	FDA	+160 /-20
1002	Indoor	8 0	0.080	60	8	N/A	Clear PVC	Yes	FDA/USDA	+150/-40
1003	Indoor/Outdoor	8 0	0.080	100	8	8	Clear PVC	Yes	FDA/USDA	+150/-40
1004	Indoor	8 0	0.080	60	8	N/A	Weld Screen	No	FDA	+160/-20
1005	Indoor	8 0	0.080	60	8	N/A	Weld Screen	No	FDA	+160/-20
1010	Indoor/Outdoor	12	0.120	60	13	10	ClearPVC	No	FDA	+160/-20
1011	Indoor/Outdoor	12	0.120	100	13	10	ClearPVC	No	FDA	+160/-20
1012	Indoor	12	0.120	60	13	10	Clear PVC	Yes	FDA/USDA	+150/-40
1013	Indoor	12	0.120	100	13	13	ClearPVC	Yes	FDA/USDA	+150/-40
1020	Indoor/Outdoor	16	0.160	60	20	17	ClearPVC	No	FDA	+160/-20
1021	Indoor/Outdoor	16	0.160	100	20	20	ClearPVC	No	FDA	+160/-20
1022	Indoor/Outdoor	16	0.160	60	20	17	ClearPVC	Yes	FDA	+160/-20
1023	Indoor/Outdoor	16	0.160	100	20	20	Clear PVC	Yes	FDA	+160/-20

Flexible, hanging strips push open and close instantly to minimize air transfer and slash utility bills. Alternating concave/convex strips effect a good seal and provide an effective barrier against birds and insects, dust, debris, drafts, smoke, fumes and noise.


Chalfant Strip Door closures can save energy and provide protection in a variety of interior and exterior commercial and industrial applications. Uses are limited only by our imagination!

The PVC strips are transparent, nontoxic and smooth edged for safety and retain their flexibility to -200 F or 400 F depending upon strip material.

Suggested Specifications:

Chal-Strip Door closures as manufactured by Chalfant Sewing Fabricators, Inc., PH 216-521-7922 shall be Model _____ for door or areas _____ wide x _____ high. Mounting shall be doorway type or surface type and hung from galvanized steel hardware angle.

Mounting Types (All Steel*)



* Aluminum hardware available on request. Must specify option.

Whether You Need 1 or 100... Chalfant Is Ready To Handle Your Project
For Additional Information Or Assistance In Specifying Your Loading Dock Equipment, Contact The Factory.
Other Chalfant Products: Dock Bumpers, Wheel Chocks And NEW Guardian Rain Shield!



Dock Bumpers & Wheel Chocks



Dock Lights



Impact Doors



"Quality Made, Built To Last"

Authorized Distributor

11525 Madison Avenue • Cleveland, OH 44102-2325
 TEL: 216-521-7922 FAX: 216-521-6854 On The Web: www.ChalfantUSA.com