

**PART 1 - GENERAL****1.1 SUMMARY**

- A. WORK INCLUDED
  - 1. Factory wheel chock unit.
  - 2. Installation Manual.

**1.2 SUBMITTALS**

- A. General: Submit in accordance with Section 01 33 00.
- B. Product Data: Submit for wheel chock.
- C. Submit dimensional detail.
- D. Submit specification.

**1.3 QUALITY ASSURANCE**

- A. Single Source Responsibility: Provide each component of individual wheel chock per particular type by same manufacturer.
- B. Manufacturer Qualifications: Company specializing in manufacturing products specified in this Section with minimum ten years' experience.
- C. Installer Qualifications: Approved in writing by manufacturer.

**PART 2 - PRODUCTS****2.1 ACCEPTABLE MANUFACTURERS AND MODEL**

- A. Wheel Chock as provided by Chalfant Sewing Fabricators, Cleveland, OH. Contact: <http://www.ChalfantUSA.com> for project quote.

**2.2 EQUIPMENT**

- A. CONSTRUCTION: (Select one)
  - A. Black molded fiber reinforced rubber; 11" long by 9" wide by 7" high
  - B. Laminated fabric reinforced rubber pads between steel plates, 7" long by 11" wide by 7" highOptions:
  - (\_\_\_) 15'0" chain and link.
- B. WARRANTY: Unit shall include the manufacturers standard (1) one year warranty against defects in materials and workmanship on the remaining components.

**PART 3 EXECUTION****3.1 INSTALLATION**

- 1. Install in accordance with manufacturer's instructions.